

# Datenblatt

## TERM2000 MULTI IP67



Code	Power	Colour	EAN	IP	Size wxhxd in cm	Weight in kg	Cabel	Connection	Heatable area sqm	Spare Tube	Installation
RCJ330	2 x 1,65 kW	Polished aluminum	4260051480435	67	123,5 x 9,5 x 12,5	4,9	0,65m 5-wire, 1,5 mm <sup>2</sup> , wire-end sleeves	2/N/PE ~ 240 V 50 Hz	26-28	LG1650 	Wall and ceiling horizontal, Face Down, 45° mounting angle
RCJ400V	2 x 2,0 kW		4260051480442		123,5 x 9,5 x 12,5	4,9		2/N/PE ~ 400 V 50 Hz	28-30	LG2001V 	
URCJ330V	2 x 1,65 kW		4260051483870		123,5 x 9,5 x 12,5	4,9		2/N/PE ~ 240 V 50 Hz	26-28	ULG1650V 	
URCJ400V	2 x 2,0 kW		4260051483887		123,5 x 9,5 x 12,5	4,9		2/N/PE ~ 400 (2N) V 50Hz	28-30	ULG2001V 	
URCC495V	3 x 1,65 kW		4260051483894		60 x 29 x 12,5	6,8		3/N/PE ~ 400 (2N) V 50Hz	39-40	ULG1650V 	
URCC600V	3 x 2,0 kW		4260051483900		60 x 29 x 12,5	6,8		3/N/PE ~ 400 (2N) V 50Hz	42-44	ULG2001V 	